

If you are a developer, you may prefer to go directly to the [source code](#).

Requirements

- **A server**, being physical host or a virtual machine. <https://www.vpsbenchmarks.com/> can help you pick a provider. If you don't have a server: we are currently experimenting for a [Home Server](#) option.
 - CPU
 - 1 core/thread is enough for a fresh website but we suggest to consider at least 2. And scale accordingly in the future.
 - RAM
 - To run Virtualmin and a few small Tiki instances, you should have at least 2GB of RAM. But as word goes, the more the better.
 - STORAGE
 - 10GB can get you started with an OS and everything you need. But you should get more or even over-provision if you plan for an intensive online activity with lots of files.
 - Do not forget about backups: start locally and move to remote as soon as possible. Virtualmin can help you make the best out of your available space, by rotating backups.
- **A grade A GNU/Linux operating system**, stable and suitable for servers
 - You need to pre-install a **fresh minimal Debian 12**. For status on OS support, please see [here](#).
 - Do not pre-install or pre-configure any additional packages on your OS. The installer expects a freshly installed, supported, OS, and anything you do differently may cause conflicts or configuration errors. If you will be enabling third-party package repositories, do so after installation, and only with extreme caution.
- **A domain name** (a sub-domain will also do fine), with the following options:
 - At the moment it is recommended to delegate fully a working sub-domain or domain to the server before your proceed, because your WikiSuite server will run flawlessly a BIND nameserver. In this case you will have the advantages of creating subdomains easily, locally, also with SPF records for example. And it offers flexibility for any future domains.
 - You can also point a wildcard subdomain if you don't want to deal with DNS on your server. For example, if we want all requests pointed to test.wikisuite.org or *.test.wikisuite.org as this makes it easy to create many projects, such as: abc.test.wikisuite.org, def.test.wikisuite.org, etc.
 - Last but not least, for a single (sub)domain just a simple A and/or CNAME record from your DNS provider pointed to your IP. This is provider-dependent and not covered here.

You'll want something like this:

test	A record	(put your IP address here)
*.test	CNAME	test.wikisuite.org.

More info at [Set up your domain name](#)

How WikiSuite leverages Virtualmin / Webmin

Webmin is a web tool to facilitate server management. [Virtualmin](#) extends Webmin with a focus on shared hosting, which allows multiple instances of [Tiki Wiki CMS Groupware](#) that are clearly segmented.

Installing WikiSuite automatically installs all the necessary packages and Webmin which itself automatically installs Virtualmin (both configured for optimal settings for WikiSuite components, see here the [Differences between Virtualmin and WikiSuite](#)).

If you have an unreliable internet connection, you should use [tmux](#) or something similar. (So you can launch some commands, and they continue running even if you are disconnected).

Getting started

Log in to your server via SSH with the root user. In some cases, your host may not provide you a **root** access to directly login to, but a user such as **debian**. This is why commands which require root are pre-fixed by [sudo](#).

Quick installation

Quickly install WikiSuite package with just with few steps.
Then:

Download script

```
wget -O wikisuite-installer.bash https://gitlab.com/wikisuite/wikisuite-packages/-/raw/main/wikisuite-installer.bash
```

Then :

Run the script

```
bash wikisuite-installer.bash
```

Optionally run the script with option

```
wikisuite-installer.bash -ft all wikisuite-installer.bash -ft none wikisuite-installer.bash -ft dns wikisuite-installer.bash -ft  
ssl,dns,mail,ftp
```

If for some reason, the quick script doesn't work for your use case, or you want more control on your install, please see the next section for the standard installation.

Standard Installation

Proceed with the installation process manually by following all the steps required.
Before the installation process, update and upgrade the system to ensure packages are current.

Update and upgrade the system

```
apt-get update && apt-get upgrade
```

Then:

If you get -bash: sudo: command not found, install it first as root user

```
apt-get install sudo
```

This installs curl if not already installed

```
sudo apt-get install curl
```

Check your host name

```
sudo hostnamectl
```

Set a proper FQDN hostname for your machine. This domain name needs to be active, and pointing to this machine

WikiSuite: The most comprehensive and integrated Open Source enterprise solution.

```
sudo hostnamectl set-hostname machinename.example.org
```

This downloads the install script (which you can inspect)

```
curl -o wikisuite-installer.bash https://gitlab.com/wikisuite/wikisuite-packages/-/raw/main/wikisuite-installer.bash
```

This is to inspect the script (optional)

```
nano wikisuite-installer.bash
```

This runs the install script

```
sudo bash wikisuite-installer.bash
```

There is also support for [NGINX](#) available.

A web URL for accessing Virtualmin will be provided after installation is complete **Ex:** <https://your-ip-address:10000> (GUI is at port 10000)

After completing the Virtualmin post-install wizard **Ex:** <https://yourdomain:10000> (GUI is at port 10000) becomes available.

If you are getting SSL errors: Virtualmin -> Select base domain -> Server Configuration -> SSL Certificate -> Let's Encrypt -> Request Certificate

You now have a WikiSuite server. Congrats!

This could be a good time to reboot your server, and make sure it restarts fine.

You will get kicked out. Reconnect after reboot.

```
sudo reboot
```

Next steps:

1. Create a [Virtual Server](#) for your Tiki, based on a plan
2. Use Tiki Manager to install [Tiki Wiki CMS Groupware](#)

Create a Virtual Server for your Tiki

Go to **Ex:** <https://example.org:10000>

Virtualmin > Create Virtual Server

For more info: <https://www.virtualmin.com/documentation/tutorial/virtual-server-basics>

Fill in the appropriate fields and **make sure you check the "Tiki Manager" feature!** Then click the "Create Server" button and you are done.

← ? ☆ Create Virtual Server

New virtual server type: **Top-level server** Sub-server Alias of dome.lab8.evolutadata.com Alias of dome.lab8.evolutadata.com, with own email

▼ New virtual server details

Domain name
my.example.com

Description
My Example Tiki

Administration password

SSH public key
☒ No default key ☐ Generate private and public keys ☐ Use public key below ..

Server configuration template
WikiSuite 1 with www alias

Account plan
WikiSuite 1

Administration username
☒ Automatic ☐ Custom username

► Advanced options

▼ Enabled features

☒ Apache website ☒ Webmin login
☒ Apache SSL website ☒ Enable AWStats reporting
☒ MariaDB database ☒ Enable Tiki Manager

► IP address and forwarding

Create Server

Handling "www" and non-"www" domains with Tiki Manager

Tiki Manager allows you to manage websites that use either the "www" prefix or not. If you want a domain like example.org to redirect and respond as www.example.org, make sure to select the appropriate **Server configuration template** when creating the virtual server.

In the Server configuration template dropdown (as shown in the image above), choose for example "WikiSuite 1 **with www alias**". This ensures that requests to the non-www version (example.org) are automatically handled as www.example.org.

If a domain name is valid, free SSL (for https://) certificates from [Let's Encrypt](https://letsencrypt.org/) are automatically created. If you'll add the domain later, you can get SSL later: Virtualmin > Select base domain > Server Configuration > SSL Certificate > Let's Encrypt > Request Certificate

So now, you should be able to visit both my.example.org and see a placeholder page. If domain name is not set up, you can [Preview Website via Virtualmin](#)

Virtualmin has many other features like domain alias, domain rename, etc. which we invite you to discover.

Installing Tiki via the included Tiki Manager feature

For more info, please see [Tiki Manager docs](#).

To access everything related to our manager you have to navigate to Services > Tiki Manager.

Just fill in the email address, note the password, choose the desired Tiki Version and hit install. The Tiki Manager will inform you that your instance is ready; you can visit it at your Virtual server URL and manage it using the username "admin" and your previously displayed password. Or you can import an existing instance.

The screenshot displays the Virtualmin web interface. On the left is a teal sidebar with a 'Webmin' button and a 'Virtualmin' dropdown menu. The 'Virtualmin' menu is expanded, showing options like 'my.example.com', 'Virtual Server Summary', 'Create Virtual Server', 'Edit Virtual Server', 'Edit Users', 'Edit Databases', 'Install Scripts', 'File Manager', 'Administration Options', 'Server Configuration', 'Disable and Delete', 'Services' (which is highlighted), and 'Logs and Reports'. The 'Services' sub-menu is also expanded, listing 'Configure SSL Website', 'Configure Website', 'PHP-FPM Configuration', 'Preview Website', 'Protected Directories', 'Tiki Manager' (which is selected), and 'Logs and Reports'. The main content area is titled 'Tiki Manager for https://my.example.com'. It features a settings icon and a heading 'Install a new Tiki instance'. Below this heading are four form fields: 'Admin email' (test@my.example.com), 'Sender email' (test@my.example.com), 'Admin password' (43EFDV19uTcmPs3asdf), and 'Select branch' (23.x). Each field has a descriptive text below it. A warning message states: 'Warning All files in "/home/my/public_html" will be deleted!'. There is an 'Install' button next to the 'Select branch' dropdown. Below the installation section is the 'Import existing instance' section, which shows 'Tiki found at: '/home/my/public_html'' and a 'Do you want to import it?' question with an 'Import' button. At the bottom of the interface are two blue buttons: 'Return to virtual server details' and 'Return to virtual servers list'.

You now also have a Tiki instance running on your WikiSuite server

See more at [Virtualmin Tiki Manager](#)

Discover. Configure. Enjoy.

The default page of Tiki:



HomePage

Congratulations

This is the default homepage for your Tiki. If you are seeing this page, your installation was successful.

You can change this page after logging in. Please review the [wiki syntax](#) for editing details.

Get started.

To begin configuring your site:

1. Log in with your newly created password.
2. Manually [Enable specific Tiki features](#) that you didn't enable with the Admin wizard.
3. Run [Tiki Profiles](#) to quickly get up and running.

Need help?

For more information:

- [Learn more about Tiki](#).
- [Get help](#), including the [official documentation](#) and [support forums](#).
- [Join the Tiki community](#).

The Tiki Admin Dashboard looks like this:

The screenshot shows a web browser window with multiple tabs. The active tab is 'Openfire Admin Console: Sys'. The address bar shows 'leonardo.mxims.net:9090/server-properties.jsp#edit'. The main content area displays a table of server properties with columns for the property name, value, and status (indicated by green plus and red minus icons). Below the table is an 'Edit property' form for 'admin.authorizedJIDs' with a text area containing 'luis.lucio@leonardo.mxims.net,mario.lozano@leonardo.mxims.net'. The form also includes a 'Property Encryption' section with radio buttons for 'Encrypt this property value' and 'Do not encrypt this property value' (selected). At the bottom of the form are 'Save Property' and 'Cancel' buttons. The footer of the page contains navigation links: 'Server | Users/Groups | Sessions | Group Chat | Plugins | Meetings' and a note: 'Built by [Jive Software](#) and the [IgniteRealtime.org](#) community'.

Property Name	Value	Status
provider.user.className	org.jivesoftware.openfire.Idap.LdapUserProvider	+
provider.vcard.className	org.jivesoftware.openfire.Idap.LdapVCardProvider	+
sasl.scram-sha-1.iteration-count	4096	+
setup	true	+
stream.management.active	true	+
stream.management.requestFreq...	5	+
update.lastCheck	1453740419042	+
voicebridge.default.proxy.outboun...		+
voicebridge.default.proxy.sipauthu...		+
voicebridge.default.proxy.sippass...	hidden	+
voicebridge.default.proxy.sipserver		+
xmpp.auth.anonymous	true	+
xmpp.domain	leonardo.mxims.net	+
xmpp.session.conflict-limit	0	+
xmpp.socket.ssl.active	true	+

Edit property

Property Name: admin.authorizedJIDs

Property Value:

Property Encryption: ☐ Encrypt this property value ☒ Do not encrypt this property value

Extras

There are

- [Special configurations with Virtualmin](#)
- [Alternative ways to automatically install Tiki](#)
- [Optional packages](#)

CLI vs web version of PHP

`sudo su -l` permits to switch to becoming root, and have the proper CLI version of PHP. Reference: <https://github.com/virtualmin/virtualmin-gpl/issues/520>

Force all traffic to SSL / HTTPS

- [Force all traffic to SSL](#)

Forcing IPv4 on apt

Sometime the installer may fail silently, not being able to talk to the repos; usually it is a network/name resolution problem, most common is accessing via IPv6, solved by:

```
sudoedit /etc/apt/apt.conf.d/99force-ipv4
```

and in the file inserting

```
Acquire::ForceIPv4 "true";
```

Forcing IPv4 for everything networking by stopping IPv6:

```
sudo nano /etc/sysctl.conf
```

Place the following entry to disable IPv6 for all adapters.

```
net.ipv6.conf.all.disable_ipv6 = 1
```

For a particular adapter (If the network card name is `enp0s3`).

```
net.ipv6.conf.enp0s3.disable_ipv6 = 1
```

To reflect the changes execute the following command.

WikiSuite: The most comprehensive and integrated Open Source enterprise solution.

```
sudo systemctl -p
```

Email

- [Set up email with Virtualmin and Cypht within Tiki](#)

Default Website for IP address

If server is accessed by IP address, you can pick which domain is shown via Server Configuration -> Website Options -> Default Website for IP address

It is recommended not to have a live site there, as end users should really use domain names, and it could be nasty bots scanning IPs to find forms to abuse. (real story!)

Find out more, ask the community for help and get involved

- Check the official website [Tiki Wiki CMS Groupware](#)